



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

General

| | |
|-------------------------------------|--|
| Provided equipment | CD with software User manual USB cable |
| Number of tare power | 45 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|--------------------|
| Depth | 54.4 cm |
| Height | 43.2 cm |
| Mounting location | Front |
| Mounting preference | No preference |
| Product weight | 55.91 kg |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | Yes |
| Width | 19.6 cm |

Input

| | |
|-------------------|--|
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Plug standard | BS1363A British IEC 320 C20 Schuko CEE 7 / EU1-16P |

| | |
|----------------------|---------------------------------------|
| Input voltage limits | 151...302 V adjustable 160...285 V |
| Input voltage | 230 V |

Output

| | |
|----------------------------------|--|
| Rated power in W | 2700 W |
| Maximum configurable power in W | 2700 W |
| Harmonic distortion | Less than 5 % |
| Output frequency | 47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Nb of power socket outlets | 8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19 |
| Efficiency | 95 % (full load) |
| Output voltage | 230 V |
| Maximum configurable power in VA | 3000 VA |
| Rated power in VA | 3000 VA |
| Transfer time | 2 ms typical |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 53 dBA |
| Heat dissipation | 375 Btu/h |

Batteries & Runtime

| | |
|--|--|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |
| Number of battery replacement quantity | 1 |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Liquid value | 0 |
| Battery charger power | 271 W rated |
| Battery power in VAh | 816 VAh runtime |
| Battery life | 3...5 year(s) |
| Extended runtime | 0 |

Communications & Management

| | |
|---------------|--|
| Control panel | LED status display with on line : on battery : replace battery and overload indicators |
| Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|-------------------|--|
| Surge energy rate | 365 J |
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------------------|-------|
| Package 1 Weight | 65 kg |
| Package 1 Height | 68 cm |
| Package 1 width | 38 cm |
| Package 1 Length | 76 cm |
| Number of Units in Package 3 | 3 |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|