

Specifications for imageRUNNER 3225

Main Unit		
Imaging System	Laser Dry Electrostatic Transfer System	
Image Server Memory	512MB + 256MB (std) 1024MB + 768MB (max.)	
Hard Disk Drive	60GB	
Network Interface Connection	10 / 100 / 1000Base-TX, USB2.0	
First Copy Time	Less than 4.9 seconds	
Warm-up Time	35 seconds (max.)	
Copy / Print Speed	25ppm (A4)	
Max. Original Size	A3	
Max. Copy Size	A3	
Min. Copy Size	A5	
Max. Mail Boxes Supported	100	
Max. Copy Reservation	10	
Resolution	300 x 300dpi (Colour Scan) / 600 x 600dpi (optional) 600 x 600dpi (BW Scan) 1200 interpolated dpi x 600dpi (Copy) 1200 x 1200dpi (Print)	
Halftone	256 Gradations of Gray	
Magnification	25% to 400% (in 1% increment)	
Paper Supply (80gsm)	Standard:	Dual 550 sheets Paper Cassette, 50 sheets Stack Bypass
	Optional:	Dual 550 sheets Paper Cassette, 2,700 sheets Paper Deck (4,950 sheets max.)
Acceptable Paper Weight	Cassette:	64 - 90gsm
	Bypass:	64 - 128gsm
Exposure Control	Automatic or Manual	
Multiple Copies	1 to 999	
Dimensions (H x W x D)	761 x 565 x 700mm	
Weight	74.0kg	
Power Source	220 - 240V / 6A / 50 - 60Hz	
Power Consumption	Less than 1.41KW	
Drum	75,000 sheets (A4)	
Toners (at 6% coverage)	21,000 sheets (A4)	