

Overview

N9K-C9336PQ is the Nexus 9336 ACI Spine switch with 36p 40G QSFP. The Cisco Nexus 9336PQ ACI Spine Switch is a 2-Rack-Unit (2RU) spine switch for Cisco ACI that supports 2.88 Tbps of bandwidth and 2.3 billion packets per second (bps) across 36 fixed 40 QSFP+ ports. Cisco Nexus 9300 platform leaf switches are Layer 2 and 3 nonblocking 10 and 40 Gigabit Ethernet switches with up to 2.56 Terabits per second (Tbps) of internal bandwidth.


Quick Specs

Table 1 shows the Quick Specs.

Product Code	N9K-C9336PQ
Physical	<ul style="list-style-type: none">● 36-port 40G QSFP ports● 1200 watt (W) AC power supplies or 930W DC power supplies (up to 2)● 80 Plus Platinum-rated power supplies that provide at least 90% efficiency with 20% utilization● Hot-swappable, dual fan trays with redundant fans● Port-side intake or Port side exhaust airflow direction● System memory: 16GB● SSD: 64GB● USB: 2 ports● RS-232 serial console ports: 1● Management ports: 1 x 10/100/1000BASE-T
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)
Weight (chassis)	34.4 lb


Product Details

Figure 1 shows the front panel of N9K-C9336PQ.



Note: (1) 36 40-Gigabit QSFP+ ports (2) USB ports (3) Out-of-band management port (RJ-45 port) (4) Console port (RJ232 port)

Figure 2 shows the back panel of N9K-C9336PQ.



Note: (1) Power supplies (2) (AC power supply shown) (2) Fan modules (2)

The Accessories

Table 2 shows the supported accessories.

Model	Description
N9K-C9300-FAN3	Nexus 9300 Fan 3, Port-side Intake
N9K-C9300-FAN3-B	Nexus 9300 Fan 3, Port-side Exhaust
NXA-FAN-160CFM-PI	Nexus Fan, 160CFM, port side intake airflow
NXA-FAN-160CFM-PE	Nexus Fan, 160CFM, port side exhaust airflow
NXA-FAN-35CFM-PI	Nexus Fan, 35CFM, port side intake airflow
NXA-FAN-35CFM-PE	Nexus Fan, 35CFM, port side exhaust airflow
N9K-PAC-1200W	Nexus 9300 1200W AC PS, Port-side Intake
N9K-PAC-1200W-B	Nexus 9300 1200W AC PS, Port-side Exhaust
NXA-PAC-1100W-PE2	Nexus 1100W AC PS, Port-side Exhaust
NXA-PAC-1100W-PI2	Nexus 1100W AC PS, Port-side Intake
NXA-PAC-1200W-PE	Nexus 1200W AC PS, Port-side Exhaust
NXA-PAC-1200W-PI	Nexus 1200W AC PS, Port-side Intake
N9K-PUV-1200W	Nexus 1200W, 200-277AC,240-380DC, Dual airflow PSU
UCS-PSU-6332-DC	930W -48V DC PS, Port-side Exhaust
UCSC-PSU-930WDC	930W -48V DC PS, Port-side Intake
NXA-PDC-930W-PE	Nexus 930W -48V DC PS, Port-side Exhaust
NXA-PDC-930W-PI	Nexus 930W -48V DC PS, Port-side Intake

Compare to Similar Items

Table 3 shows the comparison.

Product Code	N9K-C9336PQ	N9K-C9332C
--------------	-------------	----------------------------

Physical	<ul style="list-style-type: none">● 36-port 40G QSFP ports● 1200 watt (W) AC power supplies or 930W DC power supplies (up to 2)● 80 Plus Platinum-rated power supplies that provide at least 90% efficiency with 20% utilization● Hot-swappable, dual fan trays with redundant fans● Port-side intake or Port side exhaust airflow direction● System memory: 16GB● SSD: 64GB● USB: 2 ports● RS-232 serial console ports: 1● Management ports: 1 x 10/100/1000BASE-T	<ul style="list-style-type: none">● 32-port 40/100G QSFP28 ports & 2-port 1/10G SFP+ ports● 1100 watt (W) AC, DC or HVAC/HVDC power supplies (up to 2)● Hot-swappable, 5 fans with redundancy● System memory: 16 GB● SSD: 256GB● USB: 1 port● RS-232 serial console ports: 1● Management ports: 2 (1 x 10/100/1000BASE-T and 1 x 1-Gbps SFP+)● Broadwell-DE CPU: 4 cores
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)	1.7 x 17.3 x 22.9 in. (4.4 x 43.9 x 58.1 cm)
Weight (chassis)	34.4 lb	25.1lb (11.4kg) with power supplies and fans, 19 lb (8.6kg) without power supplies and fans

Get More Information

Do you have any question about the Cisco N9K-C9336PQ?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

N9K-C9336PQ Specification		
Physical	<ul style="list-style-type: none">● 36-port 40G QSFP ports● 1200 watt (W) AC power supplies or 930W DC power supplies (up to 2)● 80 Plus Platinum-rated power supplies that provide at least 90% efficiency with 20% utilization● Hot-swappable, dual fan trays with redundant fans● Port-side intake or Port side exhaust airflow direction● System memory: 16GB● SSD: 64GB● USB: 2 ports● RS-232 serial console ports: 1● Management ports: 1 x 10/100/1000BASE-T	
Power and Cooling	<ul style="list-style-type: none">● Power: 1200W AC, 930W DC or 1200W HVAC/HVDC● Input voltage: 100 to 240V* AC or -40V to -72V DC (min-max), -48V to -60V DC (nominal) <p>*Supports input voltage of 100-120V for a max output of 800W; 200-240V for a max output of 1200W</p> <ul style="list-style-type: none">● Frequency: 50 to 60 Hz (AC)● Efficiency: 90% or greater (20 to 100% load)● RoHS compliance: Yes● Hot swappable: Yes● Port-side intake or port-side exhale options● Typical power: 400W (AC)● Maximum power: 660W (AC)	
Environmental	<ul style="list-style-type: none">● Physical (H x W x D): 3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)● Weight: 34.4 lb● Operating temperature: 32 to 104°F (0 to 40°C)● Nonoperating (storage) temperature: -40 to 158°F (-40 to 70°C)● Humidity: 5 to 95% (noncondensing)● Altitude: 0 to 13,123 ft (0 to 4000m)	
Acoustics	<ul style="list-style-type: none">● Fan speed at 40%: 64.4 dBA● Fan speed at 70%: 79.6 dBA● Fan speed at 100%: 89.8 dBA	
MTBF	<ul style="list-style-type: none">● 242,000 hours	
Regulatory compliance	Products should comply with CE Markings according to directives 2004/108/EC and 2006/95/EC	

Safety	<ul style="list-style-type: none"> ● UL 60950-1 Second Edition ● CAN/CSA-C22.2 No. 60950-1 Second Edition ● EN 60950-1 Second Edition ● IEC 60950-1 Second Edition ● AS/NZS 60950-1 ● GB4943
EMC: Emissions	<ul style="list-style-type: none"> ● 47CFR Part 15 (CFR 47) Class A ● AS/NZS CISPR22 Class A ● CISPR22 Class A ● EN55022 Class A ● ICES003 Class A ● VCCI Class A ● EN61000-3-2 ● EN61000-3-3 ● KN22 Class A ● CNS13438 Class A
EMC: Immunity	<ul style="list-style-type: none"> ● EN55024 ● CISPR24 ● EN300386 ● KN 61000-4 series
RoHS	The product is RoHS-6 compliant with exceptions for leaded-Ball Grid-Array (BGA) balls and lead press-fit connectors

Download Resource

Support and Resources

 [Cisco Nexus 9300 ACI Fixed Spine Switches Datasheet](#)

Transition Guide

 [Select and Upgrade Cisco Data Center Switch](#)

Want to Buy

Order Now

Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



16,000+

Customers Trusted



200+

Countries we Sold



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com

