



## A NEW ERA OF LARGE-FORMAT PRINTING BEGINS HERE.

One good printing experience is all it takes to set a new standard. The Epson SureColor™ SC-P10070 and SC-P20070 professional production printers are designed to give you the best results. Epson's Advanced PrecisionCore™ MicroTFP® printhead technology yields high speeds of up to 17.5 m<sup>2</sup>/h\*, with accurate dot placement for stand-out visuals. To top it all, Epson's UltraChrome™ PRO nine-colour pigment ink system delivers vibrant prints with lasting durability, while a high-precision media feeding system ensures smooth, reliable operations.



SC-P10070



SC-P20070



2.64"  
Printhead



Up to  
64" Wide\*\*



Versatile  
Media  
Handling



Up to  
1.5mm  
Thick



Ethernet



## ENGINEERED FOR BUSINESS

### Rapid Speeds For Maximum Output

New PrecisionCore MicroTFP printhead utilises 8000 nozzles for class-leading print speeds of up to 17.5 m<sup>2</sup>/h\*.

### Affordable Prints with Peace of Mind

Epson's UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Cost-effective 700ml ink cartridges ensure low printing costs.

### Precision Media Feeding System

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.



PRECISIONCORE

EPSON ULTRACHROME  
**PRO** INK

\*Based on 6-pass printing for high quality production, on photo media.

\*\*Up to 64" wide for P20070, 44" for P10070.

# SPECIFICATIONS

## SURECOLOR™ SC-P10070/P20070


**EPSON**  
EXCEED YOUR VISION

Model Number	SC-P10070	SC-P20070
Printer Width	44"	64"
Printing Technology	PrecisionCore™ MicroTFP Printhead	
Printhead	Nozzle Verification System	
Printing Method	Black colour ink : 4,000 nozzles (PK, MK, DGY, GY, LGY 800 nozzles each colour)	
Nozzle Configuration	Colour ink : 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)	
Print Direction	Bi-directional printing, uni-directional printing	
	Auto Head Alignment technology	
Print Quality	2400x1200 dpi	
Maximum Resolution	3.5pl	
Minimum Ink Droplet Volume		
Performance*1		
Draft Mode	600 x 600dpi, 1.9 minutes	
Normal Mode	1200 x 1200dpi, 3.0 minutes	
Fine Mode	2400 x 1200dpi, 5.6 minutes	
Ink System	Epson UltraChrome™ PRO Ink	
Ink Type	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan, Vivid Light Magenta	
Colours		
Ink Capacity	700ml/110ml (Bundled)	
Printer Software on CD-ROM		
Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / MacOSX10.6.8 or later	
	Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later	
	2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later (Certification/Logo : Windows Server 2008/2008R2)	
Paper Handling		
Paper Feed Method	Friction Feed	
Roll Dimensions	170mm	
Paper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44")	Roll paper : 254mm (10") - 1626mm (64")
	Cut sheet : 210mm (A4)- 1118mm (44") 0.08-1.50mm	
Borderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 1030mm(B0), 1118mm(44in/B0+)	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.), 1372mm(54), 1524(60in.)
Roll Paper Remaining	The remaining amount is managed by the barcode print on Roll paper.	
Control Panel		
Colour & Size	2.7" Colour LCD	
Number of Dots	960 x 240 pix.	
Connectivity		
Standard	Hi-Speed USB	
Ethernet	1000BASE-T (Recommended) / 100BASE-TX	
Control Code	ESC/P raster	
Memory		
Main	1GB	1.5GB
Software		
PC Software	User's Guide(EN) Network Guide(EN) , LFP RemotePanel 2, EpsonColorCalibrationUtility, EpsonNet Setup, EpsonNet Config, EpsonNet Print (Windows only)	
Printer Web Function	'Remote Manager' HDD utility - Control of HDD functions	
Software from Web Download	LFP Accounting Tool (Job monitoring, consumable cost tracking), HDD Utility software (Web download)	
Electrical Specifications		
Voltage	AC100-240V 50/60Hz	
Rated Current	5A	
Power Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interface is 1000BASE-T; Power off (Stand-by): Less than 0.5W	
Recommended Operating		
Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C	
Humidity	Operating: 20% - 80% (no condensation); Storage: 5% - 85% (no condensation)	
Acoustic Noise Level		
Sound Pressure Level	Approx 50.5dB (A)	Approx 51.1dB (A) less than
Sound Power Level	Approx 65.3dB (A)	Approx 67dB (A) less than
System Requirement	Windows XP/Vista/7/8/8.1 (32/64bit) or later	
	CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB	
	Macintosh Mac OS X10.6.8 or later	
	CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB	

### Dimensions & Weight


#### SC-P10070

Weight: 126kg



### SC-P20070

Weight: 171kg



\*1 Figures represent print times only for Epson test sample image (A1 size) as shown, produced on Premium Photo paper.



A1:588x735mm

### Ink Cartridge Compatibility

#### 700 ml Ink Cartridges

● Photo Black	C13T809100
● Cyan	C13T809200
● Magenta	C13T809300
● Yellow	C13T809400
● Light Cyan	C13T809500
● Vivid Light Magenta	C13T809600
● Dark Grey	C13T809700
● Matte Black	C13T809800
● Grey	C13T809900
● Light Grey	C13T809000

### Supplies & Optional Accessories

Auto Cutter Spare Blade	C13S210040
Cleaning Stick	C13S090013
Maintenance Box	C13T619300
Auto Take-up Reel Unit	C12C932201
Roll Adapter	C12C932231
Adobe® PostScript® 3™	
Expansion Unit	C12C891131
Hard Disk Unit	C12C848031



©2016 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

### EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1,  
Murphy Road, Ulsoor, Bangalore - 560 008.  
Tel: 080-30515000 Fax: 080-30515005

CONTACT EPSON TODAY! EMAIL: vasu@eid.epson.co.in

SOUTH Alok Singh 098405 03210 NORTH Akhtar Imam 099101 08780, Ashutosh Kumar 098153 94550,

Sudhir Kumar 093898 35156 EAST Sourov Kumar 098746 72616 WEST Milind 098209 74733



**Epson Helpline:** For product info or service - 1800 425 0011  
For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat)  
Email: lfp@epsonindia.in

www.epson.co.in

### Regional Offices:

Ahmedabad - 2640 7176/77, Chennai - 3967 7500, Cochin - 4012 315,  
Coimbatore - 98942 19200, Indore - 4701 830, Kolkata - 6500 9370/77, Mumbai - 3079 8200,  
New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41

Dealer's Stamp

Information correct at  
time of printing  
Printed August 2016

