# HP Colour LaserJet Pro M154 Printer series



Quickly produce outstanding colour documents – and get easy mobile printing – for a great value.

Get vibrant colour fast print speeds, and increased mobility to drive efficiency – for a great value.<sup>2</sup>







HP Colour LaserJet Pro M154nw



#### **Access fast colour printing**

- Get fast print speeds and rapid first page out time (FPOT).
- Help save energy with HP Auto-On/Auto-Off Technology.3
- Change paper less often with a 150-sheet capacity paper tray.



#### More. Performance and Protection.

- Count on high-quality colour with Original HP Toner cartridges with JetIntelligence.
- Get the Original HP quality you paid for with anti-fraud technology.
- Speed through print jobs right out of the box, using preinstalled Original HP Toner cartridges.




#### Easy mobile printing and scanning – HP Smart app

- Print and scan from your smartphone, and easily order toner, with the HP Smart app.5
- Have confidence in your connection with steady performance from dual band Wi-Fi<sup>®</sup>.<sup>1</sup>
- Connect your smartphone or tablet directly to your printer and easily print without accessing a network.<sup>6</sup>
- Simply tap the print button on your smartphone or tablet to print.<sup>2</sup>

<sup>&</sup>lt;sup>1</sup> Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at http://www.hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. <sup>2</sup> For details on local printing requirements see http://www.hp.com/go/mobile printing <sup>3</sup> HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade. <sup>4</sup> Based on cartridge yields for HP 201A compared with HP 204A Original HP LaserJet Toner Cartridges. For more information, see http://www.hp.com/go/learnaboutsupplies <sup>5</sup> Requires the HP Smart app download. Features controlled may vary by mobile device operating system. Full list of supported operating systems and details at http://support.hp.com/us-en/document/c03561640. For details on local printing requirements see http://www.hp.com/go/mobileprinting <sup>6</sup> Mobile device needs to be connected to Wi-Fi Direct® signal of a Wi-Fi Direct-supported AiO or printer prior to printing. Details at http://www.hp.com/go/mobileprinting. Wi-Fi Direct® is a registered trademark of Wi-Fi Alliance®.

## **Product walkaround**

- 1. 100-sheet output bin
- 2. 150-sheet input tray
- 3. LED control panel with intuitive button controls
- 4. Front door (access to toner cartridges)
- 5. Wi-Fi Direct®1
- 6. Easy mobile printing with the HP Smart App<sup>2</sup>
- 7. Power connection
- 8. USB 2.0 port
- 9. Ethernet port
- 10. Dual Band wireless networking<sup>3</sup>



**HP Colour LaserJet Pro M154nw** 

# Series at a glance





Model	HP Colour LaserJet Pro M154a	HP Colour LaserJet Pro M154nw
Product number	T6B51A	T6B52A
Print speed (A4) Black/colour⁴	Up to 16/16 ppm	Up to 16/16 ppm
Control panel	Button and LED display	Button and LED display
150-sheet input tray, 100-sheet output bin	Yes	Yes
Wi-Fi Direct mobile printing¹	Not available	Yes
Dual Band Wi-Fi³	Not available	Yes
Cartridge yield, black/colour (in pages) <sup>5</sup>	In-box: ~800/700 A: ~1,100/900	In-box: ~800/700 A: ~1,100/900

<sup>&</sup>lt;sup>1</sup> Mobile device needs to be connected to Wi-Fi Direct<sup>®</sup> signal of a Wi-Fi Direct-supported AiO or printer prior to printing. Details at hp.com/go/mobileprinting. Wi-Fi Direct<sup>®</sup> is a registered trademark of Wi-Fi Alliance<sup>®</sup>. The HP Colour LaserJet Pro M154a model does not offer Wi-Fi Direct. <sup>2</sup> Requires the HP Smart App download. Features controlled may vary by mobile device operating system. Full list of supported operating systems and details at http://support.hp.com/us-en/document/c03561640. For details on local printing requirements, see hp.com/go/mobileprinting. The HP Colour LaserJet Pro M154a model does not offer mobile printing. <sup>3</sup> Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting. Wi-Fi® is a registered trademark of Wi-Fi Alliance<sup>®</sup>. The HP Colour LaserJet Pro M154a model does not offer Dual Band wireless networking. <sup>4</sup> Measured using ISO/IEC 24734; excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>5</sup> Replacement 204A cartridge average composite (C/Y/M) declared yield ~900 and average black yield ~1,100 pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.

## **HP Colour LaserJet Pro M154 Printer series**

Model	HP Colour LaserJet Pro M154a	HP Colour LaserJet Pro M154nw		
Functions	Print	Wireless, Print		
Print		THE COST CHIC		
Speed	Black (A4, normal): Up to 16 ppm;			
Speca	Colour (A4, normal): Up to 16 ppm			
First page out	Black (A4, ready): As fast as 11.5 sec; Black (A4, sleep): As fast as 13.8 sec Colour (A4, ready): As fast as 13.4 sec; Colour (A4, sleep): As fast as 15 sec	Black (A4, ready): As fast as 12 sec; Black (A4, sleep): As fast as 12.5 sec Colour (A4, ready): As fast as 13.5 sec; Colour (A4, sleep): As fast as 13.9 sec		
Technology	Laser			
Resolution (Black/colour, best)	Up to 600 x 600 dpi			
Mobile printing capability	No	HP ePrint; Apple AirPrint™; Mopria™-certified; Wireless Direct Printing; Mobile Apps		
Wireless capability	No	Built-in 802.11 b/g/n; authentication via WEP, WPA/WPA2, or 802.11x; encryption via AES or TKIP; WPS; Wi-Fi Direct		
<b>Ca</b> rtridges number	4 (1 each black, cyan, magenta, yellow)			
Languages	HP PCL 6, HP PCL Sc, HP postscript level 3 emulation, PCLm, PDF, URF			
Management	HP Printer Assistant (UDC); HP Utility (Mac); HP Device Toolbox; HP JetAdvantage Security Manager			
Connectivity				
Connectivity	Hi-Speed USB 2.0 port	Hi-Speed USB 2.0 port; built-in Fast Ethernet 10/100Base-TX network port; 802.11n 2.4/5GHz wireless		
Network Capabilities	No	Yes, via built-in 10/100 Base-TX Ethernet; authentication via 802.11x		
Memory (Maximum)	128 MB DDR, 128 MB NAND Flash			
Processor speed	800 MHz			
Media	1			
Duty cycle	Up to 30,000 pages			
Recommended Monthly Page Volume	150 to 1500			
Paper handling	150-sheet input tray, 100-sheet output bin			
Туре	Paper (bond, brochure, coloured, glossy, heavy, letterhead, light, photo, plain, preprinted, prepunched, recycled, rough), transparencies, labels, envelopes, cardstock			
Weight	60 to 163 g/m² (Uncoated/Matte, recommended), however up to 175 g/m² Postcards and 200 g/m² HP Matte is allowed in the driver; 60 to 163 g/m² (Coated/Glossy, recommended), however up to 175 g/m² Postcard and 220 g/m² HP Glossy is allowed in the driver.			
Sizes custom	76 x 127 to 216 x 356 mm			
Dimensions (W x D x H)	392 x 379.6 x 244.2 mm			
Weight	13.3 kg			
Systems				
Compatible operating systems		ection, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, CD-ROM/DVD el® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD		
	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/igo/unixmodefscripts)	nand line installer and supports Win Server 2008 R2 and higher. Apple® 05 X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see		
Minimum system requirements	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip	nand line installer and supports Win Server 2008 R2 and higher. Apple® 05 X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see onnection, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space,		
	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet COD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® YSP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided.	nand line installer and supports Win Server 2008 R2 and higher. Apple® 05 X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see onnection, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space,		
Minimum system requirements  Security management  Control panel	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comm (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet CO-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® YS PS a rhigher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided  Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB	and line installer and supports Win Server 2008 R2 and higher. Apple® 05 X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see   onnection, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, only), any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, of via the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPV1 community password change; HP ePrint: HTTPS with certificate		
Security management	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet CO-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® YSP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provide Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB No	and line installer and supports Win Server 2008 R2 and higher. Apple® 05 X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Unix (For 233 MHz compatible processor, 850 MB available hard disk space, of via the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 110%), 50 Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz); 260-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); Valta (41-3		
Security management  Control panel Power	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the corne (V10.11), Sosemite (V10.11), So GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, B.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP S93 or higher (32-bit) CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provide Mac: Apple® 0S X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB No  Button and LED display  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+7 - 10%), 50 Hz (+7 - 3 Hz), 60 Hz (+7 - 3 Hz),	and line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Unix (For more information, see onnection, USB port, Internet Explorer. Windows Vista®; (32-bit only), 2 GB available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, of via the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/ - 10%), 50 Hz (+/ - 3 Hz), 50 Hz (+/ - 3 Hz), 50 Hz (+/ - 3 Hz), 60 Hz (-/ - 3 Hz), 60		
Security management  Control panel Power  Software included	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PCE Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet CO-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® Server support is provider Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB  No  Button and LED display  Power supply type: Internal (Built-in) power supply, Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 3 Hz), 60 Hz (+/- 3 Hz); 7 Hz), 60 Hz (+/- 3 Hz); 8 Hz), 8 Hz, 9 H	nand line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, see see opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Unix (For more information, see opensource.com/hplip-web/index.html). Windows Vista® (32-bit only), 2 GB available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, of via the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; IH ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/ - 10%), 50 Hz (+/ - 3 Hz), 60 Hz (+/ - 3 Hz); 70 Hz (		
Security management  Control panel  Power  Software included  Acoustics	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comm (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, 8.1, 8.7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® Server support is provider Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB  No  Button and LED display  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 70 Hz (+/- 3 H	and line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, only): any Intel® Pentium® II. Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, of via the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply: Power supply required: 110-volt input voltage: 110 t 127 VAC (*/- 10%), 50 Hz (*/- 3 Hz); 60 Hz (*/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (*/- 10%), 50 Hz (*/- 3 Hz)) for Using the Value of Using Value of Usin		
Security management  Control panel  Power  Software included  Acoustics	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PCE Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provide Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB  No  Button and LED display  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 109%), 50 Hz (+/- 3 Hz), 60 Hz (+/-	and line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, 25 de available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, of the third of the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply: Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 1096), 50 Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 1096), 50 Hz (+/- 3 Hz) (Not dual voltage; product varies by part number with # Option code identifier); Power consumption <sup>2</sup> : 343 watts (active printing), 6.0 (ready), 0.7 watt (sleep), 0.1 (Manual-Off), 0.1 (Auto-off/Manual-on), 0.6 (Auto-off/Wake on LAN); Typical electricity consumption (TEC) number: ES 0.453 kWh/Week; BA: 0.458 kWh/Week; (DXP), HP Web Services Assist (HP Connected), Device Setup & Software, HP Printer Assistant, HP Product  Acoustic pressure emissions bystander (active, printing): 48 dB(A)(Colour); 48 dB(A)(mono); retting humidity range: 0 to 95% RH; Operating humidity range: 10 to 80% RH; Recommended		
Security management  Control panel	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comm (V10.11), Vosemite (V10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PC: Windows® 10, 8.1, 8.7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® VR 993 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® VR 993 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® Server support is provided Mac: Apple® 05 X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB No  Button and LED display  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 70 Hz (+/- 3	and line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, 90 SX: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, 90 SX: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, 90 SX: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Windows Vista®: (32-bit tonly), 2 GB available hard disk space, only): any Intel® Pentitim® III, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, olive the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; IP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 200-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 60 Hz (+/- 3 Hz); 80 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Lidentifier); Power consumption <sup>2</sup> ; 243 watts (active printing), 60 (ready), 0.7 watt (sleep), 0.1 (Manual-Off), 0.1 (Auto-Off/Manual-In), 0.6 (Auto-Off/Make on LAN); Typical electricity consumption (TEC) number: ES 0.453 kWn/Week; BA: 0.458 kWn/Week  (DXP), HP Web Services Assist (HP Connected), Device Setup & Software, HP Printer Assistant, HP Product  Acoustic pressure emissions bystander (active, printing): 48 dB(A)(Colour); 48 dB(A)(mono);  rating humidity range: 0 to 95% RH; Operating humidity range: 10 to 80% RH; Recommended  TCP/IR; IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing Discovery; EP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6		
Security management  Control panel  Power  Software included  Acoustics  Environmental ranges	drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provided via the comn (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB. Linux (For more information, see http://hplip.http://www.hp.com/go/unixmodelscripts)  PCE Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer 8. Windows Server support is provide Mac: Apple® OS X Sierra(v10.12), El Capitan (v10.11), Yosemite (v10.10); 1.5 GB HD; Internet required; USB  No  Button and LED display  Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 109%), 50 Hz (+/- 3 Hz), 60 Hz (+/-	and line installer and supports Win Server 2008 R2 and higher. Apple® OS X: Sierra(v10.12), El Capitan opensource.com/hplip-web/index.html). Unix (For more information, 23 BHz compatible processor, 850 MB available hard disk space, only): any Intel® Pentium® II. Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, olivia the command line installer and supports Win Server 2008 R2 and higher.  Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change; H9 ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication; Firewall and ACL; SNMPv3  Power supply type: Internal (Built-in) power supply: Power supply required: 110-volt input voltage: 110 t 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); C20-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); C20-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); C20-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); C30		

¹ Introductory cartridges included, ~800 page yield black and ~700 page yield colour composite (C/Y/M). ² Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device ³ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device. ⁴ Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled. ⁵ Replacement 204A cartridge average composite (C/Y/M) declared yield ~900 and average black yield ~1100 pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies

### **HP Services**

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs.

Choose from:

# Optimized Care (optimum performance and stability):

4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

#### Standard Care (high level of uptime):

Next Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

# Basic Care (minimum recommended support):

Next Business Day Onsite Support

#### 4 hour Onsite Support:

Onsite support within four hours after a service call received within the coverage window

#### **Next Business Day Onsite Support:**

Onsite service the next business day after the service call is received

#### **Maintenance Kit Replacement Service:**

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

# Installation with Network Configuration Service:

Assembly, network configuration, and basic administrator familiarization. For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices



















## **Top Features**

Achieve colour printing at fast speeds – for an affordable price.

Print outstanding colour and help protect your MFP, using Original HP Toner cartridges with JetIntelligence.

Print and scan from your smartphone, and easily order toner, with the HP Smart app. Get a stable, reliable wireless connection with dual band Wi-Fi®.

**Product** 

**T6B51A** HP Colour LaserJet Pro M154a **T6B52A** HP Colour LaserJet Pro M154nw

**Supplies** 

CF510A HP 204A Black Original LaserJet Toner Cartridge (1,100 pages)
CF511A HP 204A Cyan Original LaserJet Toner Cartridge (900 pages)
CF512A HP 204A Yellow Original LaserJet Toner Cartridge (900 pages)
HP 204A Magenta Original LaserJet Toner Cartridge (900 pages)

#### **HP Care Packs**

UG086EHP 3 year Care Pack w/Next Day Exchange for LaserJet PrintersUG481EHP 3 year Care Pack w/Onsite Exchange for LaserJet PrintersUG289EHP 3 year Care Pack w/Return to Depot Support for LaserJet PrintersU6N05EHP Installation with Networking Service for Consumer Printer

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

#### **HP Inc offices**

Australia China	(613) 8833 5000 (010) 6564 3888	hp.com.au hp.com.cn
Hong Kong	(852) 3077 2688	hp.com.hk
India Indonesia	(80) 2612 9000 (62-21) 5799 1088	hp.com/in hp.com/id
Korea	(02) 2199 0114	hp.co.kr
Malaysia	(603) 2332 3333	hp.com.my
New Zealand	(09) 918 9555	hp.co.nz
Philippines	(632) 888 5900	hp.com/ph
Singapore	(65) 6275 3888	hp.com.sg
Taiwan	(02) 8722 9000	hp.com.tw
Thailand	(662) 353 9500	hp.com/th
Vietnam	(848) 3823 4151	hp.com/vn

• Cambodia • Maldives • Nepal • Pakistan • Srilanka For more information, please visit us at <a href="https://example.com/">https://example.com/</a> apac/homeandoffice

#### **HP Order-a-Cartridge**

Call HP's Order-a-Cartridge<sup>3</sup> service and have them conveniently delivered to your doorstep.

China 800 820 0851/400 820 0851


India 1800 3003 3003 Korea 080 703 0700

#### **HP SureSupply<sup>3</sup>**

Discover how HP SureSupply rede ines convenience in purchasing printer cartridge supplies online. To order online, please visit hp.com/apac/oac for more details.<sup>3</sup>

#### To learn more, visit hp.com

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.





<sup>1</sup> Requires the HP Smart app download. Features controlled may vary by mobile device operating system. Full list of supported operating systems and details at http://support.hp.com/us-en/document/c03561640. For details on local printing requirements see http://www.hp.com/go/mobileprinting

<sup>&</sup>lt;sup>2</sup> Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at http://www.hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. The HP Colour LaserJet Pro MFP M180n model does not offer Dual Band wireless networking.

<sup>&</sup>lt;sup>3</sup> Available in selected countries only.