

Wide-angle Full HD Camera

KX-VD170

Full-HD 12x Optical zoom/10x digital zoom 72.5° Horizontal wide-angle



KEY FEATURES

- Full-HD
- 12x Optical zoom/10x digital zoom 72.5° Horizontal wide-angle
- Pan range: $\pm 130^\circ$ /tilt range: $+90^\circ/-25^\circ$
- Ceiling mount possible
- Can be controlled from the remote control of HDVC System

The KX-VD170 camera, in combination with the HD Video Conference system, delivers smooth, high-resolution 1080/60p Full-HD and wide-angle images.

When used with the optional KX-VCZ170 Ceiling bracket, this camera also can be mounted on the ceiling.

Ideal for large conference rooms for 10 to 20 people

SPECIFICATIONS

Lens	Motorized 12x zoom, F1.8 to 2.8(f=3.9 mm to 47.3 mm {5/32 inch to 1-55/64 inch})
Focus	Switching between auto and manual
Imaging Sensors	1/2.8?type Full?HD CMOS
Focus Distance	Entire zooming range: 1.5 m {4.92 feet}
Horizontal Resolution	900 TV lines Typ (Center area, Wide)
Output Format	HD 1080: 59.94p HD 1080: 50p
Panning Range	±130°
Field of View	Horizontal 72.5° (Wide) – 6.3° (Tele) Vertical 44.9° (Wide) – 3.8° (Tele)
White Balance Function	Provided
[Pan-Tilt Head Unit] Pan/Tilt Operation Speed	Max. 90°/s or more
Storage Temperature	-20 °C to +50 °C {-4 °F to +122 °F}
Video Output	HDMI (HDMI connector)
Input Connector	DC 12 V IN
Quietness	NC35 (normal speed), NC40 (when preset)
Tilting Range	+90°/-25°
Ambient Operating Temperature	0 °C to +40 °C {+32 °F to +104 °F}
Finish	Silver
Dimension (W x D x H)	180 mm x 145 mm (excluding the projections) x 184 mm {7?3/32 inches x 5?45/64 inches x 7?1/4 inches}
AC Adaptor Input	AC 100 V to 240 V, 0.5 A to 0.3 A, 50 Hz/60 Hz
AC Adapter Output	DC 12 V, 1.5 A
Allowable Humidity Ranges	20 % to 90 % (no condensation)
Mass	Approx. 1.6 kg {3.53 lbs.}

URL: <https://business.panasonic.co.uk/visual-system/Wide-angle-Full-HD-Camera/KX-VD170>

CONTACT

Web: <https://business.panasonic.co.uk/visual-system/contact-us>