

16-Port 10/100Mbps GREENnet Switch

- **Hardware**
- **Standards**
 - IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX; IEEE 802.3x Flow Control
- **Network Media**
 - Ethernet: UTP/STP Cat. 3, 4, 5, up to 100m
 - Fast Ethernet: UTP/STP Cat. 5, 5e, 6, up to 100m
- **Data Rate**
 - Ethernet: 10Mbps/20Mbps (half/full-duplex)
 - Fast Ethernet: 100Mbps/200Mbps (half/full-duplex)
- **Protocol / Topology**
 - CSMA/CD, Star
- **Power Consumption**
 - 6 watts (max.)
- **Switch Fabric**
 - 3.2Gbps forwarding capacity
- **Interface**
 - 16 x 10/100Mbps Auto-MDIX RJ-45 ports
- **RAM Data Buffer**
 - 1.25Mbits

- **Filtering Table**
 - 8K entries
- **Diagnostic LED**
 - Power, Link/ACT, 100Mbps
- **Power**
 - 100~240VAC, 50~60Hz, 0.4A Internal Power Supply
- **Dimension**
 - 440 x 140 x 44mm (17.3 x 5.5 x 1.7in.)
- **Weight**
 - 1.72kg (3.8lb)
- **Temperature**
 - Operating: 0° ~ 50° C (32° ~ 122° F)
 - Storage: -10° ~ 70° C (14° ~ 158° F)
- **Humidity**
 - Operating: 10% ~ 90% (Non-Condensing)
 - Storage: 5% ~ 90% (Non-Condensing)
- **Certifications**
 - CE, FCC

Package Contents

- TE100-S16g
- Multi-Language Quick Installation Guide
- Power cord
- Rackmount kit