

3D Printing Filament

Top grade 3D printing filament, manufactured to very tight tolerances. Made from the highest quality materials to ensure consistent feeding and stable prints.

Verbatim is part of the Mitsubishi Chemical Holdings Group, one of the world's leading manufacturers of plastics.



Verbatim PLA Filament 1.75mm 1kg



Products Information

- PLA (Polylactic Acid) filament is a degradable bioplastic derived from plants.
- Guaranteed not to have heavy metals, phthalates or BPA.
- Suited for a wide range of 3D printers
- All filament is delivered in a vacuum bag, with desiccant, wound onto a spool.
- Heated build platform not required.
- Made in Japan.

System specifications

Diameter accuracy:	1.75 ± 0.05 mm
Process temperature:	200-220 ° C (recommended)
Net Weight:	1 kg
Gross Weight:	1.5 kg (includes spool and corrugated box)
Filament Length:	334 metres
Spool Dimensions:	
Spool Diameter:	200mm
Spool Depth:	72mm
Hub Diameter:	102mm
Hub Hole Diameter:	51mm

Verbatim PLA Filament 3mm 1kg



Products Information

- PLA (Polylactic Acid) filament is a degradable bioplastic derived from plants.
- Guaranteed not to have heavy metals, phthalates or BPA.
- Suited for a wide range of 3D printers
- All filament is delivered in a vacuum bag, with desiccant, wound onto a spool.
- Heated build platform not required.
- Made in Japan.

System Specification

Diameter accuracy:	2.95 ± 0.05 mm
Process temperature:	200-220 ° C (recommended)
Net Weight:	1 kg
Gross Weight:	1.5 kg (includes spool and corrugated box)
Filament Length:	119 metres
Spool Dimensions:	
Spool Diameter:	200mm
Spool Depth:	72mm

Hub Diameter:	102mm
Hub Hole Diameter:	51mm

Verbatim ABS Filament 1.75mm 1kg



Products Information

- ABS (Acrylonitrile Butadiene Styrene) filament is a copolymer which is made of styrene, acryl and butadiene.
- It is impact resistant and tough.
- Suited for a wide range of 3D printers
- All filament is delivered in a vacuum bag, with desiccant, wound onto a spool.
- Heated build platform recommended (80 to 120 °C).
- Made in Japan.

System Specification

Diameter accuracy:	1.75 ± 0.05 mm
Process temperature:	230-240 °C (recommended)
Net Weight:	1 kg
Gross Weight:	1.5 kg (includes spool and corrugated box)
Filament Length:	404 metres
Spool Dimensions:	
Spool Diameter:	200mm
Spool Depth:	72mm
Hub Diameter:	102mm
Hub Hole Diameter:	51mm