

## Output

---

- Output Voltage Distortion  
Less than 5%
- Output Frequency (sync to mains)  
47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
- Output Connections  
(6) IEC 320 C13 (Battery Backup)
- Max Configurable Power (Watts)  
500 Watts / 750 VA
- Output power capacity  
500 Watts / 750 VA
- Topology  
Line Interactive
- Output Voltage Note  
Configurable for 220 : 230 or 240 nominal output voltage
- Waveform type  
Sine wave
- Transfer Time  
2ms typical

## Input

---

- Input frequency  
50/60 Hz +/- 3 Hz (auto sensing)
- Input voltage adjustable range for mains operation  
151 - 302 V
- Input voltage range for main operations  
160 - 285 V
- Input Breaker Capacity  
0 A
- Input Connections  
IEC-320 C14

## Battery

---

- Battery type  
Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
- Efficiency

---

[View Efficiency Graph](#)

## Runtime

---

- Output power capacity  
500 Watts / 750 VA

## Physical

---

- Maximum Depth  
361 mm , 36.1 CM
- Maximum Height  
157 mm , 15.7 CM
- Net Weight  
13.18 KG
- Units per Pallet  
24.0
- Shipping Depth  
500 mm , 50.0 CM
- Shipping Height  
290 mm , 29.0 CM
- Shipping weight  
6.61 KG
- Shipping Width  
270 mm , 27.0 CM
- Maximum Width  
137 mm , 13.7 CM

## Sustainable Offer Status

---

- RoHS  
Compliant
- REACH  
REACH: Contains No SVHCs